

VoIP SOLUTIONS MODELO 5516 TELEFONO IP SECRETARIAL

ANSEL DISEÑA Y FABRICA LA MAYOR GAMA DE EQUIPOS VOIP. EL 5516 ES UN TELÉFONO IP DE ALTO PERFORMANCE.

FUNCIONES SOBRESALIENTES:

	/ G.729A/G.729B CODEC ALGORITHM
<ul style="list-style-type: none"> • IDEAL PARA CONFERENCE CALL 	<ul style="list-style-type: none"> • LCD DISPLAY: DIAL DATA_CALLER NAME _CALLER NUMBER AND SO ON
<ul style="list-style-type: none"> • PUEDE REGISTRAR 3 CUENTAS SIP DE MANERA SIMULTÁNEA 	<ul style="list-style-type: none"> • VOLUMEN ADJUSTABLE PARA HANDSET AND SPEAKER
<ul style="list-style-type: none"> • FUNCIONES FORWARD/ BUSY FORWARD/ NO ANSWER 	<ul style="list-style-type: none"> • SETTINGS POR HTTP WEB BROWSER
<ul style="list-style-type: none"> • LUZ DE MENSAJE EN COMBINACIÓN CON EL PBX IP 	<ul style="list-style-type: none"> • VPN SOPORTA PPTP (OPCIONAL)
<ul style="list-style-type: none"> • AVISO DE LLAMADA ENTRANTE 	<ul style="list-style-type: none"> • SOPORTA ASTERISK OPEN SOURCE IP PBX
<ul style="list-style-type: none"> • CONFERENCE CALL: 3-WAY CALL 	<ul style="list-style-type: none"> • SOPORTA IP PBX
<ul style="list-style-type: none"> • FUNCION SPEED DIAL 	<ul style="list-style-type: none"> • SPEED DIAL:10
<ul style="list-style-type: none"> • CALL WAITING 	<ul style="list-style-type: none"> • DIAL PLAN SETTING
<ul style="list-style-type: none"> • AGENDA TELEFÓNICA PARA 140 NÚMEROS 	<ul style="list-style-type: none"> • SOPORTA HOTLINE SETTING
<ul style="list-style-type: none"> • CALL FORWARD: ALL FORWARD/ BUSY FORWARD/ NO ANSWER FORWARD BLOCK SETTING: ALL/ BY TIME/ DURATION. 	<ul style="list-style-type: none"> • SOPORTA ALARM SETTING
<ul style="list-style-type: none"> • AJUSTE PARA VOLUMEN 	<ul style="list-style-type: none"> • LAN INTERFACE: 10MBPS/100MBPS
<ul style="list-style-type: none"> • 4 TIPO DE TONOS 	<ul style="list-style-type: none"> • WAN INTERFACE : 10MBPS/100MBPS
<ul style="list-style-type: none"> • SUPORTA SIP PROTOCOL 	<ul style="list-style-type: none"> • FUENTE DE PODER: INPUT_100-240V /50/60HZ, OUTPUT_DC12V /1A
<ul style="list-style-type: none"> • UPGRADE POR FTP/TFTP/HTTP SOPORTA AUTO PROVISION BY FTP/TFTP/HTTP 	<ul style="list-style-type: none"> • US/EURO/UK/AUSTRALIAN STYLE AVAILABLE.
<ul style="list-style-type: none"> • SUPORTA G.711/ G.723.1 / G.726 	<ul style="list-style-type: none"> • PHONE BODY COLOR: BLACK
	<ul style="list-style-type: none"> • LCD SIZE: 2 X 16
	<ul style="list-style-type: none"> • OPERATIONAL TEMPERATURE: 0 TO +40°C
	<ul style="list-style-type: none"> • STORAGE TEMPERATURE: -10 TO +50°C
	<ul style="list-style-type: none"> • RELATIVE HUMIDITY: 10-90% NON-

CONDENSING
• UNIT DIMENSIONS/WEIGHT: 23.5CM× 21CM× 8.8CM/ 0.8KG
• BOX DIMENSIONS/WEIGHT:33.8CM X 20.7CM X 7.4CM/0.4KG
• SHIPPING CARTON (10 PIECES)DIMENSIONS/ WEIGHT: 43CM×38.5CM×34.5CM/1KG
• COMPLIANCE: FCC/CE/LVD
• FUNCTION KEYS: 25 FUNCTION KEYS BESIDES STANDARD KEYS 0-9,#, _
• SIP V1 (RFC2543), V2(RFC3261)
• IP/TCP/UDP/RTP/RTCP
• IP/ICMP/ARP/RARP/SNTP
• TFTP CLIENT/DHCP CLIENT/ PPPOE CLIENT
• TELNET/HTTP SERVER
• DNS CLIENT
• VLAN SETTING
• DMZ SETTING
• VIRTUAL SERVER
• MAC CLONE SETTING
• RING TONE
• RING BACK TONE
• DIAL TONE
• BUSY TONE
• USER PROGRAMMING TONE
• VOLUME ADJUSTMENT
• SPEED DIAL, PHONE BOOK
• FLASH
• SPEAKER PHONE
• CPC (CALLING PARTY CONTROL)
• G.711: 64K BIT/S (PCM)
• G.723.1: 6.3K / 5.3K BIT/S
• G.726: 16K / 24K / 32K / 40K BIT/S (ADPCM)
• G.729A: 8K BIT/S (CS-ACELP)
• G.729B: ADDS VAD & CNG TO

G.729
• STATIC IP
• DHCP
• PPPOE
• VAD: VOICE ACTIVITY DETECTION
• CNG: COMFORTABLE NOISE GENERATOR
• LEC: LINE ECHO CANCELLER
• PACKET LOSS COMPENSATION
• ADAPTIVE JITTER BUFFER
• HTTP 1.1 BASIC/DIGEST AUTHENTICATION FOR WEB SETUP
• MD5 FOR SIP AUTHENTICATION (RFC2069/ RFC 2617)
• TOS FIELD
• CALL HOLD
• CALL WAITING
• CALL FORWARD
• CALLER ID
• 3-WAY CONFERENCE
• STUN
• WEB BROWSER
• CONSOLE/TELNET
• KEYPAD
• IN-BAND DTMF
• OUT-OF BAND DTMF
• SIP INFO
• REGISTRAR SERVER (THREE SIP ACCOUNT)
• OUTBOUND PROXY
• TFTP
• CONSOLE
• HTTP
• FTP
• AUTO FIRMWARE UPDATE
• GARANTÍA 1 AÑO CONTRA DEFECTOS DE FABRICACIÓN